

Mino Dryer

烘干装置

Printing machine series

丝网印刷机械

■ 特长: Feature

- 干燥物的表里的温度是均一的，可以得到
- 安定的效果，而且防止灰尘，损伤。
- 用热风控制印刷物的表里温度均一
- 每一个单元的热风都有单独的PID控制
- 每一个单元的空气是经过过滤的清洁空气
- 活动梁式输送，防止灰尘
- 确实锁住印刷物边缘的架子
- 组装自由的复合单元式
- 架子速度50mm, 75mm 常用温度80度，150度等可调节式
- The temperature on the drying surface is even and achieve stable drying quality with dust free and anti-scratch device.
- Using hot air to control the even drying temperature on material surface.
- Using the single unit of hot air controlled by individual PID
- Using the single unit of air filter to ensure all air contains no dust
- Movable ULC delivery system with dust free
- Device for ensuring products to be hanged property on the ULC
- Section assembling
- Speed : 50mm, 75mm, constant temperature is 80 degree, 150 degree also can adjustable



HANGER DRYER

印刷物在垂下的状态中进行烘干，不会接触任何面。

里头装有活动梁，进行行走式运动烘干。

Printing material will be hanged vertically and dried. It will have no any contact.

It consists the movable conveyor and movable to the drying section

AT YOUR SERVICE SINCE 1946

MINO INTERNATIONAL LTD