

Stencil making series

丝网印刷制版机械

# T&D绷网干燥机

## T&D Tensioner and Dry



1000 × 1200 1000 × 2000


制版用绷网机，工作台，感光胶的干燥成为一体的机械。  
It is a machine could perform Tensioner and Drying.

### ■ 特长：Feature

- 省占地面积，可以省1/2
- 可以吸收制版中发生的臭味，排气。根据吸引空气的流动加速干燥时间
- 使丝网的各个点的张力均匀，而且慢速进行拉的工作，不会发生丝网撕裂现象。
- 装有张力计量记和可以得到超高张力的3S绷网机
- 用MCM感光涂布机的感光胶以均一厚度使它进行干燥的水平放置式干燥设施
- 完美的干燥效果
- Save space
- The ozone air will be exhausted and drying time is increased its speed according to the actual air current.
- Screen Tension evenness is over all the point. Gradual and slow stretching will not cause the break of the fabric.
- Build in MPA control and tension could be secured with 3S tension clamp.
- If using Mino MCM coating machine, evenness sensitive coating could beachieved and put it drying horizontally could further secure the ink layer from the stencil.
- Perfect Drying Result.

### ■ 规格，技术参数 Specification/Technical Data

	T&D 1000x1200	T&D 1000x2000
最大网框尺寸 Max Frame Size	1000x1200mm	1000x2000mm
3S绷网机的个数 3S Tensioner	18个为一体 18 unit per set	24个为一体 24 unit per set
MPA系统	纵横各1台 共2台 Horizontal / Vertical : 1 each	
干燥机温度 Drying Temperature	MAX 40度 Max : 40 degree	
干燥数量(抽屜式) No. of Frame Slot	5张 5 pcs	
大小 Dimension	2200x1700mm	3100x1800mm
换气口 Pipe Diameter	100mm Φ	
电器容量 Electrical Supply	200V 3PH 4KW	200V 3PH 5.75KW

 ミノ・インターナショナル 株式会社

MINO INTERNATIONAL LTD.

ISO9001承認

4-47-54, NUKUI, NERIMA-KU, TOKYO 176-0021 JAPAN

TEL : 81-3-3577-1621 FAX : 81-3-3577-3326

China Contact : 中国联络处

Shanghai TEL : 86-21-68931791  
上海 FAX : 86-21-58731670

Shenzhen TEL : 86-769-87772010  
深圳 FAX : 86-769-8777215

Gao Yao TEL : 86-758-8512888  
高要 FAX : 86-758-8513098

Tianjin TEL : 86-22-85685121  
天津 FAX : 86-22-85685120